

SF224/SF235



Offered with a 22hp or 32.5hp engine and a choice of cutting decks measuring 1370mm or 1570mm wide, these high perormance outfront rotary mower-collectors are designed to facilitate grass cutting in the most difficult areas.

Height of cut can easily be adjusted from 25-120mm without the use of tools, using the single height adjustment lever.


An impressive 950 litre, turbine driven, high-tip collector boosts efficiency when collecting grass. Its clearance height of 2125mm provides superior access when depositing the cut grass into waste skips, collector trucks or bins.

Routine servicing and maintenance is refreshingly easy wth excellent access to the engine, radiator and service points.



KEY FEATURES				
Power:	16.1kW (22hp) or 24.2kW (32.5hp)			
Drive System:	Hydrostatic			
Special Features:	High performing collection mower with 950ltr turbine driven high tip collector, with clearance over 2.1m			







SF224/ SF235 Technical Data

		SF235		SF224
Power	Engine: Type	E3CD		E3112
	Displacement	1498cc		1123cc
_	Power	24.2kW (32.5hp)		16.1kW (22hp)
	Fuel capacity	40ltr		40ltr
Transmission	Туре	HST (Hydrostatic transmission)		HST (Hydrostatic transmission)
	Forward	15kph		15kph
	Reverse	10kph		10kph
	Four Wheel Drive	Auto or 4WD		Auto or 4WD
Brakes	Туре	Dry Drum		Dry Drum
Tyres	Tyre Type	Turf		Turf
	Front	23x 10.50-12		23x 10.50-12
	Rear	18x 8.50- 8		18x 8.50- 8
Dimensions	Length	3339mm (with SCMB60)		3121mm (with SCMA54)
	Width	1562mm (with SCMB60)		1441mm (with SCMA54)
	Overall height	1176mm (with ROPs 2120mm)		1176mm (with ROPs 2120mm)
	Weight (inc mower)	1270kg		1180kg
Mower Deck SCMB60	No of blades		2	
	Туре		Rotary Rear Discharge	
	Cutting width		60″	
	Adjustment		1 action lever	
	Cutting height		25mm - 120mm	
Mower Deck SCMA54	No of blades		2	
	Туре		Rotary Rear Discharge	
	Cutting width		54″	
	Adjustment		1 action lever	
	Cutting Height		25mm - 120mm	
Mower Deck SSM54	No of blades		3	
	Туре		Rotary Rear Discharge	
	Cutting Width		54″	
	Adjustment		Pin Type	
	Cutting Height		25mm- 120mm	
MU-COLLECT Vario Flail	Cutting Width		140cm (162cm transport width)	
	PTO Shaft speed		1000rpm	
	Number of v-belt		2	
	Number of blades		24 (Carbide M-shackle f	ilail)
	Rotor Diameter		11cm (31cm effective dia	ameter)
	Weight		223kg	
Collector SBC950	Capacity		950ltr	
	Dump & Lift		Hydraulic	
	Dump height		2125mm	
	Blower		Turbine	

ISEKI UK & Ireland 3-5 Foxtail Road Ipswich IP3 9RT Tel: +44 (0)1473 599266 www.iseki.co.uk

